


Technical data sheet

Article number:
596-97006

TAG40-30TD1



Product Group	Self-laminating labels, thermal transfer
Product Family	Helatag 1232
Material	Type 1232, Polyester, white transparent, self-laminating (1232)
Colour	Yellow (YE)
Adhesive	Acrylic
Application Method	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.
Chem. Material Properties	Resistant to water, alcohol, gasoline, cleaning solutions and hydraulic oils.
Curing Temperature	from +2 °C
Height (H)	30.00 mm
Labels per Row	1 pc.
Material Durability	10 years external weathering (central European climate)
Mech. material properties	Due to its flexibility particularly suitable for identification of cables.
Operating Temperature	-40 °C to +150 °C
Package Content packed in	pcs.
Pack Cont.	2000 pcs.
Print Method	thermal transfer print
Recommended Ribbon Type	TT822OUT
Resistance to	Brake cleaner: 720h (at room temperature), Alcohol 94%: 720h (at room temperature), Hydraulic oil: 720h (at room temperature)
Thermal Transfer Printer	TT431, TT4030
Thickness of Foil	50 µm
UV-Stabilised	Yes
Width of Liner (WL)	44.00 mm
Width (W)	40.00 mm

