

Technical data sheet

Article number:
597-63263

PS3-H



Product Group	Prohibition signs
Product Family	HELASIGN, Material 150
Material	Type 150, Vinyl (150)
Colour	White (WH)
Adhesive	Acrylic
Adhesive strength	Stainless steel: 15-19 N/25 mm (FTM 1)
Application Method	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.
Chem. Material Properties	self extinguishing, resistant to oils, water and solvents
Curing Temperature	from +10 °C
Diameter (D)	50.00 mm
Initial tack [Test method]	110 g/cm ² [ASTM D2979-71]
Labels per Sheet	5 pcs.
Operating Temperature	-40 °C to +80 °C
Package Content packed in	pack
Pack Cont.	100 pcs.
Peel strength [Test method]	550 N/m [PSTC 7]
Self adhesive (Yes/No)	Yes
Shear strength [Test method]	120 h [FINAT FTM 7]
Storage conditions	50% relative humidity., The storage in the original packaging is recommended., Please avoid warehousing under impacts such as high humidity, heat and coldness.
Thickness of Foil [Test method]	80 µm [ASTM D3652-83]
Width of Liner (WL)	100.00 mm

