

## Technical data sheet

Article number:  
710-00115

**HTAPE-FLEX15-15x25**

|                                  |                                                                    |
|----------------------------------|--------------------------------------------------------------------|
| <b>Product Group</b>             | Vinyl Electrical Tapes –<br>Commercial Grade Vinyl Electrical Tape |
| <b>Product Family</b>            | HelaTape Flex 15                                                   |
| <b>Material</b>                  | Polyvinylchloride (PVC)                                            |
| <b>Colour</b>                    | Black (BK)                                                         |
| <b>Adhesion to Backing</b>       | 2.0 N/10 mm                                                        |
| <b>Adhesion to Steel</b>         | 2.2 N/10 mm                                                        |
| <b>Breaking Strength</b>         | 28 N/10 mm                                                         |
| <b>Dielectric Breakdown</b>      | 6.75 kV                                                            |
| <b>Dielectric Strength</b>       | 45 kV/mm                                                           |
| <b>Elongation at break</b>       | 200 %                                                              |
| <b>Length (L)</b>                | 25 m                                                               |
| <b>Operating Temperature</b>     | -10 °C to +90 °C                                                   |
| <b>Package Content packed in</b> | reel                                                               |
| <b>Pack Cont.</b>                | 25 m                                                               |
| <b>Shelf Life</b>                | 5 years                                                            |
| <b>Specifications</b>            | IEC 60454-3-1-7/F-PVCP/90                                          |
| <b>Storage Temperature</b>       | +23 °C                                                             |
| <b>Tensile Strength</b>          | 19.5 N/mm <sup>2</sup>                                             |
| <b>Thickness (T)</b>             | 0.15 mm                                                            |
| <b>Width (W)</b>                 | 15 mm                                                              |

