

## Technical data sheet

Article number:  
710-00451

**HTAPE-FLEX25-38x33**

<b>Product Group</b>	Vinyl Electrical Tapes – Insulating Tape for Higher Mechanical Requirements
<b>Product Family</b>	HelaTape Flex 25
<b>Material</b>	Polyvinylchloride (PVC)
<b>Colour</b>	Black (BK)
<b>Adhesion to Backing</b>	2.6 N/10 mm
<b>Adhesion to Steel</b>	2.6 N/10 mm
<b>Breaking Strength</b>	46 N/10 mm
<b>Dielectric Breakdown</b>	10 kV
<b>Dielectric Strength</b>	45 kV/mm
<b>Elongation at break</b>	240 %
<b>Length (L)</b>	33 m
<b>Operating Temperature</b>	-10 °C to +90 °C
<b>Package Content packed in</b>	reel
<b>Pack Cont.</b>	33 m
<b>Shelf Life</b>	5 years
<b>Specifications</b>	UL 510
<b>Storage Temperature</b>	+23 °C
<b>Tensile Strength</b>	46 N/mm <sup>2</sup>
<b>Thickness (T)</b>	0.25 mm
<b>UL-File Number</b>	E490183
<b>Width (W)</b>	38 mm

**RoHS** ✓

